WHAT IS CLAIMED IS:

1. (Amended) A method for transferring information from a network via an interface incompatible with the network to a mobile device that is compatible with both the network and the interface, the method comprising:

    establishing a communication channel between the mobile device and a switch, wherein the switch is accessible to the network and is adapted to send and receive messages compatible with both the network and interface using functionality inherited directly from the network and interface;

    receiving information from the network;

    inserting the information into a first message compatible with the interface; and

    transferring the first message to the mobile device via the interface.

2. The method of claim 1 further comprising extracting the information from the first message to recover the inserted information.

3. The message of claim 2 further comprising processing the extracted information.

4. The method of claim 1 wherein establishing the communication channel occurs prior to authenticating the mobile device in the network.

5. The method of claim 4 further comprising:

    receiving a second message from the mobile device via the interface, wherein the second message is compatible with the interface; and

    converting the second message received via the interface into information compatible with the network.

6. The method of claim 5 further comprising inserting information compatible with the network into the second message.

7. The method of claim 1 further comprising identifying a preselected field in the first message, wherein the information is inserted into the preselected field.

8. A method for manipulating data by a mobile station, wherein the mobile station is compatible with at least first and second incompatible telecommunications protocols, the

method comprising:

receiving a first message using the first protocol;

identifying information in the first message compatible with the second protocol;

extracting the identified information from the first message; and

5 processing the extracted information using the second protocol.

9. The method of claim 8 further comprising:

inserting information compatible with the second protocol into a second message compatible with the first protocol; and

10 transmitting the second message via an air interface using the first protocol.

10. (Amended) A system for enabling communications between a mobile unit and a network over an air interface, wherein the network and interface are based on first and second incompatible protocols, respectively, and wherein the mobile unit is compatible with both

15 protocols, the system comprising:

a call controller inherited directly from the network and adapted for using the first protocol;

a mobility manager inherited directly from the network and adapted for using the first protocol and accessible to the call controller;

20 at least a portion of a base station inherited directly from the interface and adapted for using the second protocol; and

a message converter accessible to the call controller and the base station portion, wherein the message converter is adapted to convert information compatible with the first or second protocol into information compatible with the other protocol.

25

11. Cancelled

12. The system of claim 10 wherein the message converter includes a plurality of instructions, including:

30 an instruction for receiving a first message based on the first protocol from the network;

an instruction for inserting the first message into a second message compatible the second protocol;

an instruction for receiving a third message based on the second protocol from the interface; and

35 an instruction for extracting a fourth message compatible with the first protocol from the

third message.

13.   The system of claim 12 further comprising an instruction for converting the third message
into a fifth message compatible with the first protocol if the third message does not contain the
5   fourth message.

14.   The system of claim 10 wherein the first protocol is a Global System for Mobile
communications (GSM) protocol and wherein the second protocol is a code division multiple
access (CDMA) protocol.
10

15.   The system of claim 10 wherein the second protocol is a Global System for Mobile
communications (GSM) protocol and wherein the first protocol is a code division multiple access
(CDMA) protocol.

15   16. (Amended) A method for transferring GSM-based information between a GSM
communications system and a GSM/CDMA compatible mobile device via a CDMA interface, the
method comprising:
        establishing a CDMA channel between the mobile device and a switch, wherein the switch
is accessible to the GSM network and adapted to send and receive both GSM and CDMA
20   messages, and wherein the switch establishes the channel using a base station system application
part and radio resource manager inherited from the CDMA interface;
        receiving, via a mobility management agent inherited by the switch from the GSM system,
        GSM-based information from the GSM network;
        inserting the information into a CDMA message; and
25   transferring the CDMA message to the mobile device via the CDMA interface.

17.   The method of claim 16 wherein establishing the CDMA channel occurs prior to
authenticating the mobile device in the GSM network.

30   18.   The method of claim 16 further comprising:
        receiving CDMA information from the mobile device; and
        converting the CDMA information into GSM information for compatibility with the GSM
network.

35   19.   The method of claim 16 wherein the CDMA message is an "ADDS Deliver" message, and

wherein inserting the GSM information into the CDMA message includes identifying a predetermined field in the "ADDS Deliver," wherein the predetermined field is used to store the GSM information.

5   20.   The method of claim 16 further comprising:

extracting the GSM information from the CDMA message; and

processing the extracted GSM information.

21. (Amended) A method for transferring CDMA-based information between a CDMA

10   communications system and a GSM/CDMA compatible mobile device via a GSM interface, the method comprising:

establishing a GSM channel between the mobile device and a switch, wherein the switch is accessible to the CDMA network and adapted to send and receive both GSM and CDMA messages, and wherein the switch establishes the channel using functionality inherited directly

15   from the GSM interface;

receiving, via functionality inherited by the switch from the CDMA system, CDMA-based information from the CDMA network;

inserting the information into a GSM message; and

transferring the GSM message to the mobile device via the GSM interface.

20

22.   The method of claim 21 wherein establishing the GSM channel occurs prior to authenticating the mobile device in the GSM network.

23.   The method of claim 21 further comprising:

25   receiving GSM information from the mobile device; and

converting the GSM information into CDMA information for compatibility with the CDMA network.

24. (New) A hybrid mobile switching center for enabling communication between otherwise

30   incompatible first and second telecommunication technologies, the hybrid mobile switching center comprising:

a call control agent inherited from the first technology;

a mobility management agent inherited from the first technology, wherein the mobility management agent is accessible to the call control agent;

35   a base station system application part and radio resource manager inherited from the

AMENDED SHEET

second technology; and

a message converter module accessible to the mobility management agent and the base station system application part, wherein the message converter module is configured to convert messages received from the mobility management agent into the second technology and messages received from the base station system application part into the first technology, and wherein the call control agent , the mobility management agent, and the base station system application part and radio resource manager are inherited from their respective technologies without altering their configuration.